

PRODUCT SPECIFICATIONS

CLASS 1 PYGMY HOG SERIES

The Pygmy Hog® 11' Self-Retracting Lifeline is a Web SRL that is manufactured from non-corrosive, lightweight components including a durable ultrahigh-molecular-weight Polyethylene (UHMWPE) & Polyester lifeline, and a durable housing made from a high strength thermoplastic polymer. The Pygmy Hog® comes equipped with a handy 360° swivel top connector, and the side lifeline exit provides a smooth and seamless payout and retraction as you move about the workspace. The Pygmy Hog® Self-Retracting Lifeline features a standard hook rebar connector and supports an ANSI worker weight capacity range of 130-310 lbs. The Pygmy Hog® is built to work as a single unit or in a kit of two with the user wearing both units at once. This OSHA and ANSI compliant, high-quality equipment is a must-have for your jobsite.



KEY FEATURES

- 1. 360° Swivel Top
- 2. Lightweight and Durable Housing
- 3. Shock Pack Cover
- 4. Polyester Lifeline
- 5. External Shock Pack
- For overhead use only
- · Fits in the Palm of Your Hand
- C1000 Carabinar Included with Singles
- C1004 Dual Connector Carabiner Included with Duals

PERFORMANCE SPECIFICATIONS

Worker Capacity Range	130-310 lbs. Max
Max Arresting Force	1,600lbf
Average Arresting Force	1,100lbf
Max Arresting Distance	42"

MATERIALS SPECIFICATIONS

OSHA

Cable		Polyester Lifeline	
Hook		Alloy Steel	
Housin	g	High-Impact Resistant Polymer	
FALL PROTECTION STANDARDS			
ANSI	ANSI/ASSP Z359.14-202	21	

1926 Subpart M, OSHA 1910, 1926.502, 1910.66

PART #	SIZE	WEIGHT
C7201-G2	11' Snap	3.9 lbs.
C7201D-G2	11' Dual Snap	8.4 lbs.
C7203-G2	11' Rebar	4.3 lbs.
C7203D-G2	11' Dual Rebar	9.2 lbs.